



AM-20 & AM-22 Digital Multimeters

- Wide range of measurement features
- Economically priced
- Large LCD display
- Compact size
- Easy to use
- Safety: CATII 600V



AM-20



AM-22

FEATURES	AM-20	AM-22	ACCURACY
AC Volts	0-199.9, 600 V	0-1.999, 19.99, 199.9, 600 V	AM-20: $\pm 2.0\%$ Rdg + 5 LSD AM-22: $\pm 1.5\%$ Rdg + 4 LSD
DC Volts	0-199.9 mV, 1.999, 0-19.99, 199.9, 1000 V		$\pm 1.0\%$ Rdg + 2 LSD
AC Amps	N/A	0-199.9 μ A, 19.99 mA, 1999 mA, 10.00 A	AM-22: $\pm 2.0\%$ Rdg + 5 LSD @ Ω /mA range**
DC Amps	0-199.9 μ A, 19.99 mA, 1999 mA, 10.00 A		$\pm 1.5\%$ Rdg + 2 LSD @ Ω /mA range**
Ohms	0-199.9 Ω , 1.999 k Ω , 19.99 k Ω , 199.9 k Ω , 1.999 M Ω , 19.99 M Ω		$\pm 0.8\%$ Rdg + 2 LSD @ 200 Ω to 2M Ω **
Continuity Buzzer	<4 Ω		
Diode Test	Open circuit test Voltage: 3.2 Volts Max. Test Current: 1.0 mA.		
Frequency	N/A	1.999 kHz, 19.99 kHz, 199.9 kHz, 1999 kHz, 1.999 MHz, 19.99 MHz	AM-22: $\pm 0.1\%$ Rdg + 2 LSD

OPTIONAL ACCESSORIES	PART NUMBER
Alligator Clips	MTC-3
Carrying Case	SV-U

REPLACEMENT PARTS <i>(supplied with product)</i>	PART NUMBER
Test Leads	MTL-6
Fuse (Special 600 Volt, 2 Amp)	6.3x25-2-12
Instruction Manual	www.AMPROBE.com

www.AMPROBE.com